



Spot		Medium		Flood		Wide Flood	
14°		28°		39°		54°	
m	ø	m	ø	m	ø	m	ø
1.0	0.25	1.0	0.50	1.0	0.72	1.0	1.02
2.0	0.49	2.0	1.00	2.0	1.43	2.0	2.04
3.0	0.74	3.0	1.50	3.0	2.15	3.0	3.06

## Flex II 3000

### Technical specification

Recessed down light with pull out spot lights for LED lamps. Reflector with four different beam spreads. Black front ring.

**Model and colors** White

**Area of use** Down light for indoor applications.

### Technical data

Mains (input) voltage	220-240 V
Total weight	2,4 kg
Form of protection	IP 20, class III
Color temperature	3 000 K
Color rendering index (CRI)	90
Light source	LED
Operating position	Vertical/retractable
Start time	Instant
Driver	Separate
Optics	Optic reflector
Beam spreads	Spot, Medium, Flood

Art no	Description	Color
280-5xx-10*	Spot, Medium, Flood or Wide flood	White
280-5xx-20*	Spot, Medium, Flood or Wide flood	Black
280-5xx-30*	Spot, Medium, Flood or Wide flood	Grey



Type	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
830	2x3000	2x26	A++
930	2x3000	2x30	A++
840	2x3200	2x26	A++
940	2x3000	2x29	A+

### Note

\*Art. nr xx = Depends on beam choices.

Product available with meat or bread COB.

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.



Saw instruction: 177 x 352 mm

A 210 B 360 C 200 (mm)