








Spot		Mediu	m	Flood	
	14°		25°		35°
m	ø	m	ø	m	ø
1.0	0.25	1.0	0.45	1.0	0.64
2.0	0.50	2.0	0.89	2.0	1.28
3.0	0.75	3.0	1.34	3.0	1.91



A 164 B 124 C 140 D 60 (mm)

## Jet micro 1200

## **Technical specification**

Track light with incorporated electronic gear and Chip on board. High quality reflector with three different beam spreads.

Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight.

**Model and colors** Available in white, black and grey. **Area of use** Track light for indoor applications.

## **Technical data**

220-240 V Mains (input) voltage Total weight 0,65 kg IP 20, class I Form of protection Color temperature 3 000 K Color rendering index (CRI) 90 Light source LED 360°/90° Operating position Start time Instant Driver Built in

Optics Metalized aluminum reflector
Beam spreads Spot, Medium, Flood

Art no	Description	Color
310-500-10	Spot	White
310-500-20	Spot	Black
310-500-30	Spot	Grey
310-501-10	Medium	White
310-501-20	Medium	Black
310-501-30	Medium	Grey
310-502-10	Flood	White
310-502-20	Flood	Black
310-502-30	Flood	Grey

Туре	Delivered lumen output (lm)	System power (W)	EEI3
830	1350	15	A+
930	1150	15	A+
840	1400	15	A++
940	1250	15	A+

## Note

Product available in other Kelvin temperatures on request.

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.