



String 3000K

Technical specification

Linear led light with housing of powder painted extruded aluminum for optimal cooling. Suitable for 3-phase track system.

Model and colors Available in white.


Area of use LED light for indoor applications, suitable for general lighting. Available for track or ceiling mounting.

Technical data

Mains (input) voltage	220-240 V
LED driver output	Constant voltage 28V, Max 60W
Total weight	2,5 kg
Form of protection	IP 20, class I
Color temperature	3 000 K
Color rendering index (CRI)	80+
Light source	LED
Operating position	Vertical
Start time	Instant
Driver	Built in
Safety glass	Included (2 different shapes available)
Beam spreads	Flood
Design lifetime	L80 B10 50 000h

B-shaped		Flat-shaped	
109°/106°		114°/107°	
m	ø	m	ø
1.0	2.64	1.0	2.70
2.0	5.29	2.0	5.41
3.0	7.93	3.0	8.11

Art no	Description	Color
227-101-009	String Led B-shaped glass	White
227-101-010	String Led flat shaped glass	White
227-101-109	String Led B-shaped glass, ceiling mounted	White
227-101-110	String Led flat shaped glass, ceiling mounted	White



Type	Delivered lumen output (lm)	System power (W)	EEI ³
830	5330 (b-shaped)	51	
830	5440 (flat-shaped)	51	

Note

Product also available with other Kelvin temperatures at request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.

Product is still under construction.

Please ask Nordic Light for latest availability update.

A 1467 B 105 C 103 D 56 E 72 (mm)