




Spot		Medium		Flood		Wide Flood	
17°		32°		41°		57°	
m	ø	m	ø	m	ø	m	ø
1.0	0.30	1.0	0.58	1.0	0.76	1.0	1.09
2.0	0.60	2.0	1.16	2.0	1.51	2.0	2.19
3.0	0.91	3.0	1.74	3.0	2.27	3.0	3.28



A 144 B 90 (mm)

Titan 4000

Technical specification

Recessed down light with chip on board and separated NL Power LED electronic ballast for optimal life time and light flow performance. High quality reflector with four different beam spreads. Lamp housing of die-cast aluminium for optimal cooling and low weight.

Model and colors Available in white, black and grey.

Area of use Down light for indoor applications.

Technical data

Mains (input) voltage	220-240 V
Total weight	0,55 kg
Form of protection	IP 20, class III
Color temperature	3000 K
Light source	LED
Operating position	Vertical/fixed
Start time	Instant
Driver	Stand alone, included
Optics	Metalized aluminum reflector
Beam spreads	Spot, Medium, Flood, Wide flood

Art no	Description	Color
271-508-10	Spot	White
271-508-20	Spot	Black
271-508-30	Spot	Grey
271-509-10	Medium	White
271-509-20	Medium	Black
271-509-30	Medium	Grey
271-510-10	Flood	White
271-510-20	Flood	Black
271-510-30	Flood	Grey
271-511-10	Wide flood	White
271-511-20	Wide flood	Black
271-511-30	Wide flood	Grey

Type	Delivered lumen output (lm)	System power (W)	EEI ³
830	4400	40	A++
930	3800	40	A+
840	4100	35	A++
940	4000	40	A++

Note

Product available with meat or bread COB on request. Product available in other Kelvin temperatures on request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.



Saw instruction: ø 128