





Spot		Medium		Flood		Wide Flood	
17°		32°		41°		57°	
m	ø	m	ø	m	ø	m	ø
1.0	0.30	1.0	0.58	1.0	0.76	1.0	1.09
2.0	0.60	2.0	1.16	2.0	1.51	2.0	2.19
3.0	0.91	3.0	1.74	3.0	2.27	3.0	3.28



Saw instruction: ø 150

A 106 B 150 C 160 (mm)

Titan L 5000

Technical specification

Recessed down light with chip on board and separated NL Power LED electronic ballast for optimal life time and light flow performance. High quality reflector with four different beam spreads. Lamp housing of die-cast aluminium for optimal cooling and low weight.

Model and colors Available in white, black and grey.

Area of use Down light for indoor applications.

Technical data

Mains (input) voltage	220-240 V
Total weight	0,85 kg
Form of protection	IP 20, class III
Color temperature	3 000 K
Color rendering index (CRI)	90
Light source	LED
Operating position	Vertical
Start time	Instant
Driver	Stand alone, included
Optics	Metalized aluminum reflector
Beam spreads	Spot, Medium, Flood, Wide flood

Art no	Description	Color
292-546-10	Spot	White
292-546-20	Spot	Black
292-546-30	Spot	Grey
292-547-10	Medium	White
292-547-20	Medium	Black
292-547-30	Medium	Grey
292-552-10	Flood	White
292-552-20	Flood	Black
292-552-30	Flood	Grey
292-553-10	Wide flood	White
292-553-20	Wide flood	Black
292-553-30	Wide flood	Grey

Type	Delivered lumen output (lm)	System power (W)	EEI ³
830	5442	50	A++
930	4664	50	A+
840	4610	40	A++
940	4997	50	A++

Note

Product available in other Kelvin temperatures on request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.