





Spot		Medium		Flood		Wide Flood	
14°		28°		39°		54°	
m	ø	m	ø	m	ø	m	ø
1.0	0.25	1.0	0.50	1.0	0.72	1.0	1.02
2.0	0.49	2.0	1.00	2.0	1.43	2.0	2.04
3.0	0.74	3.0	1.50	3.0	2.15	3.0	3.06



A 193 B 150 C 178 (mm)



Saw instruction: ø 178 mm

Twist 3000

Technical specification

Recessed down light with adjustable light direction using gyro function. Chip on board and separated NL Power LED electronic ballast for optimal life time and light flow performance. High quality reflector with four different beam spreads. Lamp housing of die-cast aluminium for optimal cooling and low weight.

Model and colors Available in white, black and grey.

Area of use Down light for indoor applications.

Technical data

Mains (input) voltage	220-240 V
Total weight	0,83 kg
Form of protection	IP 20, class III
Color temperature	3 000 K
Light source	LED
Operating position	Vertical/Gyro
Start time	Instant
Driver	Stand alone, included
Optics	Metalized aluminum reflector
Beam spreads	Spot, Medium, Flood, Wide flood

Art no	Description	Color
272-500-10	Spot	White
272-500-20	Spot	Black
272-500-30	Spot	Grey
272-501-10	Medium	White
272-501-20	Medium	Black
272-501-30	Medium	Grey
272-502-10	Flood	White
272-502-20	Flood	Black
272-502-30	Flood	Grey
272-503-10	Wide flood	White
272-503-20	Wide flood	Black
272-503-30	Wide flood	Grey

Type	Delivered lumen output (lm)	System power (W)	EEI ³
830	2900	26	A++
930	2900	30	A+
840	3000	26	A++
940	2900	29	A+

Note

Product available with meat or bread COB on request. Product available in other Kelvin temperatures on request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.