




Spot		Medium		Flood		Wide Flood	
14°		28°		39°		54°	
m	ø	m	ø	m	ø	m	ø
1.0	0.25	1.0	0.50	1.0	0.72	1.0	1.02
2.0	0.49	2.0	1.00	2.0	1.43	2.0	2.04
3.0	0.74	3.0	1.50	3.0	2.15	3.0	3.06



A 178 B 222 C 132 (mm)

## Ultra 4000

### Technical specification

Track light with incorporated electronic gear and Chip on board. High quality reflectors with four different beam spreads. Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight.

**Model and colors** Available in white, black and grey.

**Accessories** Filter

**Area of use** Track light for indoor applications.

### Technical data

Mains (input) voltage	220-240 V
Total weight	1 kg
Form of protection	IP 20, class I
Color temperature	3 000 K
Color rendering index (CRI)	90
Light source	LED
Operating position	360°/90°
Start time	Instant
Driver	Built in
Optics	Metalized aluminum reflector
Beam spreads	Spot, Medium, Flood, Wide flood

Art no	Description	Color
265-580-10	Spot	White
265-580-20	Spot	Black
265-580-30	Spot	Grey
265-581-10	Medium	White
265-581-20	Medium	Black
265-581-30	Medium	Grey
265-582-10	Flood	White
265-582-20	Flood	Black
265-582-30	Flood	Grey
265-583-10	Wide flood	White
265-583-20	Wide flood	Black
265-583-30	Wide flood	Grey

Type	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
830	4150	40	A++
930	3600	40	A+
840	3900	35	A++
940	3800	40	A++

### Note

Product available with meat or bread COB on request. Product available in other Kelvin temperatures on request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.