








Spot		Medium		Flood	
	18°		31°		42°
m	Ø	m	Ø	m	Ø
1.0	0.32	1.0	0.56	1.0	0.78
2.0	0.64	2.0	1.12	2.0	1.55
3.0	0.96	3.0	1.68	3.0	2.33



A 137 B 177 C 67 (mm)

## Ultra mini 1500

## **Technical specification**

Track light with incorporated electronic gear and Chip on board. High quality reflector with three different beam spreads. Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight.

**Model and colors** Available in white, black and grey. **Area of use** Track light for indoor applications.

## **Technical data**

220-240 V Mains (input) voltage Total weight 0,76 kg Form of protection IP 20, class I Color temperature 3 000 K Color rendering index (CRI) 90 Light source LED 360°/90° Operating position Start time Instant Driver Built in

Optics Metalized aluminum reflector
Beam spreads Spot, Medium, Flood

Art no	Description	Color
277-500-10	Spot	White
277-500-20	Spot	Black
277-500-30	Spot	Grey
277-501-10	Medium	White
277-501-20	Medium	Black
277-501-30	Medium	Grey
277-502-10	Flood	White
277-502-20	Flood	Black
277-502-30	Flood	Grey

Туре	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
830	1450	12	A++
930	1400	13	A++
840	1400	10	A++
940	1400	12	A++

## Note

Product available with meat or bread COB on request. Product available in other Kelvin temperatures by request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.